

# **KYB2003B Pressure Transmitter for Air Compressor**



### **Description:**

The product designed with advanced foreign pressure sensing element and high reliability compensation circuit, have good long-term stability. With 20 years of production technology, experience and quality of service in the field of sensor, the company has a high reputation and credibility in the industry.

### **Applications:**

Air compressor field

#### **Features:**

- ♦Using advanced foreign pressure sensing element, having stable and reliable output
- ◆Fully welded stable and reliable package structure
- ♦ Having strong ability of anti electromagnetic interference, passing EMC tests
- ◆High overload pressure, anti-shock
- ◆Outlet way flexible, convenient installation
- ◆Can be customized according to user requirements for supporting

### **Specifications:**

Product types	The diffusion silicon Pressure transmitter					
Media	Hydraulic oil, Gas, Other media compatible with 304 stainless steel					
Pressure Range	Any range in 70MPa					
Working voltage	10~30V					
Output signal	4~20mA					
Overall Error	±0.5%FS					
Overload pressure	3 X					
Burst Pressure	5 X					
Protection grade	IP65/IP67 (Waterproof plug)					
Electrical connections	The aviation connector , Hirschmann connector , users customized					




# **Order Information:**

KYB200 3	Pressure transmitter										
	В	used in air compressor field									
			Measuring range				Error				
		Code		minimum ıring range	The maximun measuring range						
		01	0~2MPa 0~5MPa 0~7MPa 0~10MPa		0∼4M	IPa		±0.5%			
		02			0∼7M	IPa		±0.5%			
		03			0~10M	⁄IPa		±0.5%			
		04			0~20MPa		±0.5%				
		05	0~	20MPa	0∼35MPa		±0.5%				
			0∼35MPa		0~60M	⁄IPa		±0.5%			
		07	0∼60MPa		0~100N	MPa	±0.5%				
			M1				4~20mA				
			V		0∼5V						
			V1		0.5~4.5V						
			V2								
			VX	u			ers customizing				
				P2	P2 M			120×1.5 External thread			
				P3			PT1/4 External thread				
				P4	G1/4 E	Externa	l thread (Dedicated to the above 20MPa range)				
				Px	users cus	stomizi	ing (Need for additional adapter)				
					C1		The a	viation connector			
					C2		Cable (S	Standard length 1m)			
					C3		Hirsc	hmann connector			
				CX			users customizing				
						-I	New edition (Must				
								options)			
								users customizing			
KYB2003	В	01	M1	P2	C2		-I	(0∼1MPa)			



## **Product Diagram:**



### **Application Picture:**



Gross Weight: 133G Net Weight: 128G