

## LDT100A(B) Electric Operating Table

### Description:

1. Adopt Taiwan imported TiMOTION electric push rod as the power source of the operation beds. The output power is large and quality is reliable.
2. Adopt German imported STABILUS as the power source of the operation beds. The output power is large and the quality is reliable.
3. Operation beds adopt Medical Grade 304# full stainless steel materials, the surface is processed through matte processing, feeling more modern, more convenient to clean.

### Specification:

Dimension: 2100\*520mm

Height of tabletop: 680mm

Tabletop lifting (up/down) (Electric): 300mm

Head and Foot tilt (Electric):  $+20^{\circ}\sim-20^{\circ}$

Lateral tilt (Electric):  $+20^{\circ}\sim-20^{\circ}$

Back plate (Manual):  $+75^{\circ}\sim-15^{\circ}$

Head Plate (Manual):  $+45^{\circ}\sim-25^{\circ}$  (detachable)

Leg plate (Manual):  $+90^{\circ}\sim-90^{\circ}$  (detachable)

### Accessories:

Square Clamp I: 5pcs

Square Clamp II: 2pcs

Arm Rest: 2pcs

Chest & Waist Supporter: 2pcs

Leg-Crutches: 2pcs

Shoulder Supporter: 2pcs

Supporter: 1pc

Note: LDT-100B has a parallel move distance of around 300mm; specification and part of the design

Optional function: Battery



[Table video on Youtube](#)

## LDT2000A(B) Electrical Hydraulic Operating Table

### Description:

1. easy to use remote controller;if no any operation within 1 min,the controller will be locked automatically to avoid mis-operation.
2. A silent,sturdy and grease-free electric hydraulic positioning system allows for multiple patients positioning.
3. The table adopts transmission X-ray materials for X-ray and C-arm use.
4. Four sections include head,back,seat and leg section,all sections applicable for X-ray use and except head section,the rest sections also have X-ray cassette layer under each section.
5. Built-in elevator kidney-bridge,which has no negative effect on X-ray radiolucency work,sup ports the kidney and gallbladder surgery efficiently.
6. Electric hydraulic brake system is more stable.
7. Compatible with many accessories.

### Specification:

Dimension : 2130\*520(mm)  
 Elevation(up/down) : 720±10(mm)  
 Lifting: 300(mm)  
 Head and Foot tilt: +30° ~ -30°  
 Lateral tilt: +20° ~ -20°  
 Head plate : +30° ~ -90°  
 Leg plate: +90° ~ -180°  
 Back plate: +75° ~ -15°  
 Sliding: 300mm  
 Kidney Bridge: 120mm

### Accessories:

Square Clamp I: 5pcs  
 Square Clamp II: 2pcs  
 Arm Rest: 2pcs  
 Chest & Waist Supporter: 2pcs  
 Leg-Crutches: 2pcs  
 Shoulder Supporter: 2pcs  
 Supporter: 1pc  
 Note: 2000B has a parallel move distance of around 300mm and kidney bridge  
 Optional function: Battery; one key reset



[Table video on Youtube](#)

## LDT3000A(B) Electric Hydraulic Operating Table

### Description:

1. Two control panels including remote panel & column panel. Panel with automatic lock if 60seconds no use and with to prevent mis-operation lock switch
2. Five section table top including Head, Back, Shoulder, Hip and Leg, all section applicable for X ray use and under each section with X ray cassette layer
3. Shoulder and Back section with composite curved kidney bridge, provide excellent operation posture of human body engineering
4. Internal battery maintaining power supply for 50-80 operations and with low battery warning function
5. Head plate and Leg plate with interchange function, can achieve table top forward position and reverse position
6. One key reset function

### Specification:

- Dimension: 2160x500mm  
 Tabletop Lifting: 650mm-1000mm  
 Head and Foot Tilt:  $-30^{\circ} \sim 30^{\circ}$   
 Tabletop Parallel Rotating:  $0^{\circ} \sim 180^{\circ}$   
 Lateral Tilt:  $20^{\circ} \sim 20^{\circ}$   
 Back Plate:  $-20^{\circ} \sim 75^{\circ}$   
 Leg Plate:  $-90^{\circ} \sim 15^{\circ}$   
 Head Plate:  $-30^{\circ} \sim 30^{\circ}$   
 Head Plate Lifting:  $\geq 140\text{mm}$   
 Built-in Kidney Bridge:  $\geq 120\text{mm}$   
 Patient Weight Capacity: 320kg  
 Battery Standby Time(h): 80  
 Sliding: 300mm(LDT3000B)

### Standard Accessories:

- Memory Mattress: 5pcs  
 Shoulder Supporter: 2pcs  
 Body Restraint Belt: 2pcs  
 Anesthesia Frame: 1pc  
 Square Clamp: 5pcs  
 Body Restraint Belt clamp: 2pcs



[Table video on Youtube](#)

## LST2000A(B) Manual Hydraulic Operating Table

### Description:

1. Manual hydraulic control system for hydraulic lock protection with low noise, high safety and reliability.
2. The table is divided into several movable segments: head plate, back plate, seat plate, leg plate. Back plate is composed of shoulder and kidney (optional). All sections adopt transmissive X-ray material, the plate below is a cassette rail, which is used for cassette radiography.
3. Built-in Kidney bridge (optional) provides convenience for gallbladder.

### Specification:

Dimension	2050*500(mm)
Elevation(up/down)	640 ~ 1100(mm)
Head and Foot tilt	+25° ~ -20°
Lateral tilt	+15° ~ -15°
Head plate	+40° ~ -90°
Leg plate	+15° ~ -90°
Back plate	+75° ~ -50°

### Accessories:

Square Clamp I:	5pcs
Square Clamp II:	2pcs
Arm Rest:	2pcs
Chest & Waist Supporter:	2pcs
Leg-Crutches:	2pcs
Shoulder Supporter:	2pcs
Supporter:	1pc

Note: LDT-2000B has a parallel move distance of around 300mm and kidney inside



[Table video on Youtube](#)