

GWIT High Temp. Insulation Silicone Coated Fiberglass Sleeve


Description

GWIT High temperature insulation Silicone Coated Fiberglass Sleeve is made of braided e-grade glass fiber, then coated with silicone resin.

The Insulation Sleeve is widely used to protect electric cables, budles and wires. It's outstanding electrical insulation, self-extinguish, water & oil proof, resist to most acid and alkali, and anti-aging, which make this kind of sleeving to be a very good choice for electrical area using.



Product characters

Thermal Class	H
Size/inner diameter:	0.5mm-50mm
Colour:	Black, red & blue, others on request 
Working temperature:	-40°C -200°C
Rate voltage:	1.5kv--7kv

Standard Size:

PART NO.	ID/mm		WALL THICK/mm	
	Nominal	Tolerance	Min.	Max.
GWIT-005	0.5	±0.15	0.35	±0.65
GWIT-008	0.8	±0.20	0.35	±0.65
GWIT-010	1.0	±0.20	0.35	±0.65
GWIT-015	1.5	±0.20	0.35	±0.65
GWIT-020	2	±0.20	0.35	±0.65
GWIT-025	2.5	±0.20	0.35	±0.65
GWIT-030	3	±0.25	0.35	±0.65
GWIT-035	3.5	±0.25	0.35	±0.65
GWIT-040	4	±0.25	0.35	±0.65
GWIT-045-	4.5	±0.25	0.35	±0.65
GWIT-050	5	±0.25	0.35	±0.65
GWIT-060	6	±0.25	0.35	±0.65
GWIT-070	7	±0.25	0.35	±0.65
GWIT-080	8	±0.30	0.5	±0.90
GWIT-090	9	±0.30	0.5	±0.90
GWIT-100	10	±0.30	0.5	±0.90
GWIT-120	12	±0.30	0.5	±0.90
GWIT-140	14	±0.50	0.5	±1.00
GWIT-160	16	±0.50	0.5	±1.00
GWIT-180	18	±0.50	0.5	±1.00
GWIT-200	20	±0.50	0.5	±1.00
GWIT-220	22	±0.60	0.5	±1.50
GWIT-240	24	±0.60	0.5	±1.50
GWIT-250	25	±0.60	0.5	±1.50
GWIT-300	30	±0.60	1	±2.00
GWIT-350	35	±0.60	1	±2.00
GWIT-400	40	±0.60	1	±2.00
GWIT-450	45	±0.60	1	±2.00
GWIT-500	50	±0.60	1	±2.00

KEYUACE



High-quality in China ✓

sales@keyuace.com

KEYUACE



High-quality in China ✓

sales@keyuace.com