

SR-N Silicone Tubing

Description

Silicone tubing is extruded and molded by environmental non-toxic silica raw materials through a special process.



Product has good performance at flexibility, abrasion and distortion and it can be resistant to many kinds of solvents, oils, acids and diluted sodium hydroxide. It can't pollute the products covered by it, quite suitable for medical, food and dairy industries.

Feature & benefit

- 1, Halogen-free environmental
- 2, Other features: electric arc resistance, corona resistance
- 3, Color: transparent, black, colorized

Product application

Applied to medical equipment, food manufacturing liquid tube and pneumatic tube, also used in household appliances, wire and cable of industrial machinery industry for providing insulation protection.

Working temperature: - 60 ° C to + 200 ° C

Dimension

Part No.	Inner diameter (mm)	Tube wall thickness of different voltage proof grade				Packaging (L)
	ID	2500V	4000V	6000V	7000V	
SR-N-0.8	0.8	0.5	1	1.5	2	200m/roll
SR-N-1.0	1	0.5	1	1.5	2	200m/roll
SR-N-1.5	1.5	0.5	1	1.5	2	200m/roll
SR-N-2.0	2	0.5	1	1.5	2	200m/roll
SR-N-2.5	2.5	0.5	1	1.5	2	200m/roll
SR-N-3.0	3	0.5	1	1.5	2	200m/roll
SR-N-3.5	3.5	0.5	1	1.5	2	200m/roll
SR-N-4.0	4	0.5	1	1.5	2	200m/roll
SR-N-4.5	4.5	0.5	1	1.5	2	200m/roll
SR-N-5.0	5	0.5	1	1.5	2	50m/roll
SR-N-5.5	5.5	0.5	1	1.5	2	50m/roll
SR-N-6.0	6	0.5	1	1.5	2	50m/roll
SR-N-7.0	7	0.5	1	1.5	2	50m/roll
SR-N-8.0	8	0.5	1	1.5	2	50m/roll
SR-N-9.0	9	0.5	1	1.5	2	50m/roll
SR-N-10	10	0.5	1	1.5	2	50m/roll
SR-N-12	12	0.5	1	1.5	2	50m/roll
SR-N-14	14	0.5	1	1.5	2	25m/roll
SR-N-15	15	0.5	1	1.5	2	25m/roll
SR-N-20	20	0.5	1	1.5	2	25m/roll

Different wall thickness and diameter silicone tube can be custom-made according to exact customers' requirements.

