

AFC-W Aluminum Foil Fiberglass Corrugated pipe

Product Introduction:

Aluminum Foil Fiberglass Corrugated pipe is made of fiberglass covered with Aluminum foil.

Properties

- 1, anti radiation heat energy, waterproof, anti-oil, anti-aging
- 2, flame resistant, high temperature resistant, resistant to vibration, light quality,
- 3, 180 degree bending, good compression and tensile properties,

Application:

- 1, widely used in construction, electric, chemical engineering, shipbuilding, aviation, textiles, metallurgy, food and other industries.
 - 2, Used for ventilation, dust extraction, smoke evacuation, gas pipeline protection.
- Continuous working temperature: 540 °C.

Standard specification:

| PART NO. | INNER DIA. (mm) | THICKNESS (mm) | Length (m) |
|----------|--------------------|-------------------|---------------|
| AFC-W-08 | 8 | 0.5 | ≤1 |
| AFC-W-13 | 13 | 0.5 | ≤1 |
| AFC-W-14 | 14 | 0.6 | ≤1 |
| AFC-W-19 | 19 | 0.6 | ≤1 |
| AFC-W-20 | 20 | 0.7 | ≤1 |
| AFC-W-25 | 25 | 0.7 | ≤1 |
| AFC-W-26 | 26 | 0.8 | ≤1 |
| AFC-W-32 | 32 | 0.8 | ≤1 |
| AFC-W-33 | 33 | 0.9 | ≤1 |
| AFC-W-40 | 40 | 0.9 | ≤1 |

