

No.	Diameter(mm)	Tensile Strength(n/mm <sup>2</sup> )	Zinc Thickness(g/m <sup>2</sup> )	Weight of unit coil(kg)
5.56	5.00	300-1400	30-100	400-800
7	4.57	300-1400	30-100	400-800
8	4.19	300-1400	30-100	400-800
9	3.76	300-1400	30-100	400-800
10	3.40	300-1400	30-100	400-800
11	3.05	300-1400	30-100	400-800
12	2.77	300-1400	30-80	400-800
13	2.41	300-1400	30-80	400-800
14	2.11	300-1400	30-80	400-800
15	1.83	300-1400	30-80	400-800
16	1.65	300-1400	30-80	25-500
17	1.47	300-1400	30-80	25-500
18	1.24	300-1400	≥12	25-500
19	1.07	300-1400	≥12	25-500
20	0.89	300-1400	≥12	25-400
21	0.81	300-1400	≥12	25-400
22	0.71	300-1400	≥12	25-200
23	0.64	300-1400	≥12	25-150
24	0.56	300-1400	≥12	10-150
25	0.51	300-1400	≥12	10-100
26	0.46	30-45	≥12	10-50
27	0.41	30-45	≥12	10-50
28	0.36	30-45	≥12	10-50
29	0.33	30-45	≥12	10-50
30	0.30	30-45	≥12	5-50
30.5	0.28	30-45	≥12	5-50