

Basic W. g/m ²	Thk. mm	Test Vol m/s	Resist ance Pa	Efficiency %			Applications
				≥ 1μm	≥2μm	≥3μm	
120	3±1	1.5	≤20	≥15	≥35	≥45	G2 Panel Filter
200	4±1	1.0	≤30	≥18	≥60	≥75	G3 Panel Filter
250	5±1	0.5	≤40	≥35	≥45	≥80	G3 Bag Filter
380	8±1	0.5	≤45	≥40	≥50	≥85	G3 Bag Filter
400	3±0.5	1.0	≤30	≥30	≥70	≥85	Safe Filter Core
260	5±1	1.0	≤35	≥25	≥25	≥60	G4 Bag Filter
400	8±1	1.0	≤55	≥45	≥85	≥90	F5 Bag Filter
570	3±0.5	1.7	≤60	≥70	≥90	≥95	Oil Filtration, Dust Collection
100	2±0.5	1.5	≤15	≥15	≥35	≥45	G3 Panel Filter
180	12±1	1.0	≤35	≥25	≥50	≥65	G3 Panel, Roll Filter
280	20±1	1.0	≤50	≥35	≥70	≥80	G4 Roll Filter
150	8±2	1.5	≤25	≥15	≥30	≥25	G2 Panel Filter
260	12±2	1.5	≤35	≥18	≥45	≥65	G3 Bag, Roll Filter
300	20±2	1.2	≤65	≥35	≥65	≥80	G4 Roll Filter
280	8±1	1.0	≤55	≥45	≥70	≥90	F5 Bag Filter
160	5±1	1.0	≤30	≥25	≥50	≥65	G3 Bag, Roll Filter
230	7±1	1.0	≤40	≥30	≥50	≥70	G4 Bag Filter