

**FS12032 Size:120\*120\*32mm DC Blower Fan**



Frame:Thermal Plastic,UL 94V-0  
 Impeller:Thermal Plastic,UL 94V-0  
 Lead Wire:AWG#24 UL1007(Optional)  
 (+):Red(-):Black

Insulation Resistance:  
 Above 10M Between Lead wire and Frame DC500V

**Specification:**

Model	Bearing	Rated voltage(v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow	Air pressure	Noise (dB)	Weight(g)
FS12032DD B12B(S)	sleeve/ball	12	1.00	12.00	2300	33.01	15.41	55.0	198
FS12032DD B12B(S)	sleeve/ball	12	0.87	10.44	2100	28.30	13.23	52.0	
FS12032DD B12B(S)	sleeve/ball	12	0.60	7.20	1800	23.64	11.00	48.0	
FS12032DD B12B(S)	sleeve/ball	12	0.49	5.88	1600	18.88	8.82	45.0	
FS12032DD B24B(S)	sleeve/ball	24	0.80	19.20	2300	33.01	15.41	55.0	
FS12032DD B24B(S)	sleeve/ball	24	0.50	12.00	2100	28.30	13.23	52.0	
FS12032DD B24B(S)	sleeve/ball	24	0.35	8.40	1800	23.64	11.00	48.0	
FS12032DD B24B(S)	sleeve/ball	24	0.28	6.72	1600	18.88	8.82	45.0	