

**FS1725 Size:172\*150\*51mm AC Axial**

Frame:Aluminum Alloy

Impeller:PBT+30%GF

Lead Wire:AWG#20 UL1015(Optional)

Motor:Shaded Pole Induction Motor

Insulation:CLASS B



## Specification:

Model	Bearing	Rated voltage(v)	Frequency (HZ)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air pressure		Noise (dB)	Weight(g)
FS-1725 H38	sleeve/ball	380	50/60	0.13	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	800
FS-1725 H23	sleeve/ball	230		0.23	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	
FS-1725 M23	sleeve/ball	230		0.18	28/27	2400/2600	7.5/9.7	0.30/0.38	45/49	
FS-1725 L23	sleeve/ball	230		0.12	21/20	2100/2400	3.0/3.9	0.12/0.16	39/45	
FS-1725 H12	sleeve/ball	120		0.45	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	
FS-1725 M12	sleeve/ball	120		0.30	28/27	2400/2600	7.5/9.7	0.30/0.38	45/49	
FS-1725 L12	sleeve/ball	120		0.15	21/20	2100/2400	3.0/3.9	0.12/0.16	39/45	

**FS1751 Size:172\*150\*51mm AC Axial Fan**

Frame:Aluminum Alloy

Impeller:PBT+30%GF

Lead Wire:AWG#20 UL1015(Optional)

Motor:Shaded Pole Induction Motor

Insulation:CLASS B



## Specification:

Model	Bearing	Rated voltage(v)	Frequency (HZ)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air pressure		Noise (dB)	Weight(g)
FS-1751 H38	sleeve/ball	380	50/60	0.13	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	800
FS-1751 H23	sleeve/ball	230		0.23	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	
FS-1751 M23	sleeve/ball	230		0.18	28/27	2400/2600	7.5/9.7	0.30/0.38	45/49	
FS-1751 L23	sleeve/ball	230		0.12	21/20	2100/2400	3.0/3.9	0.12/0.16	39/45	
FS-1751 H12	sleeve/ball	120		0.45	38/36	2600/3000	11.5/14.0	0.40/0.50	49/56	
FS-1751 M12	sleeve/ball	120		0.30	28/27	2400/2600	7.5/9.7	0.30/0.38	45/49	
FS-1751 L12	sleeve/ball	120		0.15	21/20	2100/2400	3.0/3.9	0.12/0.16	39/45	