

FS12025 Size:120*120*25mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#24 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow (CFM)/(m ³ /min)		Air pressure		Noise (dB)	Weight(g)
FS12025 DDA12B(S)	sleeve/ball	12	0.55	6.60	3000	150.11	4.20	5.82	0.23	50.0	145
FS12025 HDA12B(S)	sleeve/ball	12	0.40	4.80	2400	114.00	3.19	4.45	0.18	41.0	
FS12025 MDA12B(S)	sleeve/ball	12	0.25	3.00	2000	92.52	2.59	3.65	0.14	36.0	
FS12025L DA12B(S)	sleeve/ball	12	0.18	2.10	1800	68.45	1.92	2.68	0.11	32.0	

Shenzhen Fu Sheng Electric Co.,Ltd.
No.1,Block3,Hongchang,Shunchang Street,Pinghu,Longgang District,Shenzhen China
Tel:0755-8466-0060 Mobile:+86 13662256009

FS12025 DDA24B(S)	sleeve/ball	24	0.45	10.80	3000	150.11	4.20	5.82	0.23	50.0
FS12025 HDA24B(S)	sleeve/ball	24	0.35	8.40	2400	114.00	3.19	4.45	0.18	41.0
FS12025 MDA24B(S)	sleeve/ball	24	0.20	4.80	2000	92.52	2.59	3.65	0.14	36.0
FS12025L DA24B(S)	sleeve/ball	24	0.13	3.12	1800	68.45	1.92	2.68	0.11	32.0
FS12025 HDA48B(S)	sleeve/ball	48	0.15	7.20	3000	133.05	3.73	5.21	0.21	45.0
FS12025 MDA48B(S)	sleeve/ball	48	0.10	4.80	2700	92.52	2.59	3.65	0.14	36.0