

FS7025 Size:70*70*25mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#24 UL1007(Optional)
 (+):Red(-):Black

Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow (CFM)/(m ³ /min)		Air pressure		Noise (dB)	Weight(g)
FS7025D DA12B(S)	sleeve/ball	12	0.35	4.20	4500	36.12	1.01	4.80	0.18	42.0	50
FS7025H DA12B(S)	sleeve/ball	12	0.30	3.60	4000	32.02	0.89	4.31	0.16	40.0	
FS7025M DA12B(S)	sleeve/ball	12	0.20	2.40	3500	27.93	0.78	3.85	0.15	36.0	
FS7025L DA12B(S)	sleeve/ball	12	0.15	1.80	3000	24.00	0.67	2.65	0.10	31.0	
FS7025D DA24B(S)	sleeve/ball	24	0.30	7.20	4500	36.12	1.01	4.80	0.18	42.0	
FS7025H DA24B(S)	sleeve/ball	24	0.22	5.28	4000	32.02	0.89	4.31	0.16	40.0	
FS7025M DA24B(S)	sleeve/ball	24	0.12	2.88	3500	27.93	0.78	3.85	0.15	36.0	
FS7025L DA24B(S)	sleeve/ball	24	0.10	2.40	3000	24.00	0.67	2.65	0.10	31.0	