

FS6010 Size:60*60*10mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#26 UL1007(Optional)
 (+):Red(-):Black

Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow		Air pressure		Noise (dB)	Weight(g)
						(CFM)	(m ³ /min)				
FS6010H DA5B(S)	sleeve/ball	5	0.35	1.65	4200	15.02	0.43	1.92	0.08	28.0	25
FS6010M DA5B(S)	sleeve/ball	5	0.20	1.10	3600	13.15	0.37	1.72	0.07	27.0	
FS6010L DA5B(S)	sleeve/ball	5	0.17	0.85	3000	11.25	0.32	1.46	0.06	26.0	
FS6010H DA12B(S)	sleeve/ball	12	0.22	2.64	4200	20.25	0.57	2.55	0.10	38.0	
FS6010M DA12B(S)	sleeve/ball	12	0.17	2.04	3600	16.85	0.47	2.15	0.08	33.0	
FS6010L DA12B(S)	sleeve/ball	12	0.14	1.68	3000	13.15	0.37	1.72	0.07	27.0	
FS6010H DA24B(S)	sleeve/ball	24	0.11	2.64	4200	15.02	0.42	1.92	0.08	28.0	
FS6010M DA24B(S)	sleeve/ball	24	0.09	2.16	3600	13.15	0.37	1.72	0.07	27.0	
FS6010L DA24B(S)	sleeve/ball	24	0.07	1.68	3000	11.25	0.32	1.45	0.06	26.0	