

FS4020 Size:40*40*20mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#26 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow (CFM)/(m ³ /min)		Air pressure		Noise (dB)	Weight(g)
FS4020H DA5B(S)	sleeve/ball	5	0.28	1.40	7500	8.85	0.25	5.25	0.21	30.0	25
FS4020M DA5B(S)	sleeve/ball	5	0.25	1.25	6500	7.45	0.21	4.50	0.18	28.3	
FS4020L DA5B(S)	sleeve/ball	5	0.20	1.00	5500	6.42	0.18	3.52	0.14	26.0	
FS4020H DA12B(S)	sleeve/ball	12	1.44	1.44	7500	8.85	0.25	5.25	0.21	30.0	
FS4020M DA12B(S)	sleeve/ball	12	1.20	1.20	6500	7.45	0.21	4.50	0.18	28.3	
FS4020L DA12B(S)	sleeve/ball	12	0.72	0.72	5500	6.42	0.18	3.52	0.14	26.0	
FS4020H DA24B(S)	sleeve/ball	24	0.06	1.44	7500	8.85	0.25	5.25	0.21	30.0	
FS4020M DA24B(S)	sleeve/ball	24	0.05	1.20	6500	7.45	0.21	4.50	0.18	28.3	
FS4020L DA24B(S)	sleeve/ball	24	0.04	0.96	5500	6.42	0.18	3.52	0.14	26.0	