

**FS5015 Size:50\*50\*15mm DC Blower Fan**



Frame:Thermal Plastic,UL 94V-0  
 Impeller:Thermal Plastic,UL 94V-0  
 Lead Wire:AWG#24 UL1007(Optional)  
 (+):Red(-):Black

Insulation Resistance:  
 Above 10M Between Lead wire and Frame DC500V

**Specification:**

Model	Bearing	Rated voltage(v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow (CFM)/(m <sup>3</sup> /min)		Air pressure		Noise (dB)	Weight(g)
FS5015HD B5B (S)	sleeve/ball	5	0.35	1.75	5000	5.55	0.15	7.35	0.28	33.0	30
FS5015HD B5B (S)	sleeve/ball	5	0.22	1.10	4000	4.21	0.11	5.88	0.23	30.0	
FS5015HD B5B (S)	sleeve/ball	5	0.15	0.75	3500	3.75	0.10	5.15	0.20	28.0	
FS5015HD B12B (S)	sleeve/ball	12	0.20	2.40	5000	5.55	0.15	7.35	0.28	33.0	
FS5015HD B12B (S)	sleeve/ball	12	0.15	1.80	4000	4.21	0.11	5.88	0.23	30.0	
FS5015HD B12B (S)	sleeve/ball	12	0.10	1.20	3500	3.75	0.10	5.15	0.20	28.0	
FS5015HD B24B (S)	sleeve/ball	24	0.15	3.60	5000	5.55	0.15	7.35	0.28	33.0	
FS5015HD B24B (S)	sleeve/ball	24	0.10	2.40	4000	4.21	0.11	5.88	0.23	30.0	
FS5015HD B24B (S)	sleeve/ball	24	0.08	1.92	3500	3.75	0.10	5.15	0.20	28.0	