

FS5010 Size:50*50*10mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#26 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow		Air pressure		Noise (dB)	Weight(g)
						(CFM)	(m ³ /min)				
FS5010H DA5B(S)	sleeve/ball	5	0.30	1.50	5300	10.20	0.29	3.65	0.14	33.0	18
FS5010M DA5B(S)	sleeve/ball	5	0.20	1.00	4500	9.15	0.26	2.75	0.11	27.0	
FS5010L DA5B(S)	sleeve/ball	5	0.14	0.70	3400	7.20	0.20	2.02	0.08	21.0	
FS5010H DA12B(S)	sleeve/ball	12	0.16	1.92	5300	10.20	0.29	3.65	0.14	33.0	
FS5010M DA12B(S)	sleeve/ball	12	0.08	0.96	4500	9.15	0.26	2.75	0.11	27.0	
FS5010L DA12B(S)	sleeve/ball	12	0.07	0.84	3500	7.20	0.20	2.02	0.08	21.0	
FS5010H DA24B(S)	sleeve/ball	24	0.09	2.16	6000	10.20	0.29	3.65	0.14	33.0	
FS5010M DA24B(S)	sleeve/ball	24	0.07	1.68	5000	9.15	0.26	2.75	0.11	27.0	
FS5010L DA24B(S)	sleeve/ball	24	0.05	1.20	4000	7.20	0.20	2.02	0.08	21.0	