

FS9733 Size:97*74*33mm DC Blower Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#24 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

| Model | Bearing | Rated voltage(v) | Rated current (A) | Rated Input power(W) | Nominal speed (RPM) | Air flow | | Air pressure | | Noise (dB) | Weight(g) |
|------------------|-------------|------------------|-------------------|----------------------|---------------------|----------|------|--------------|------|------------|-----------|
| FS9733DD B12B(S) | sleeve/ball | 12 | 0.80 | 9.60 | 3200 | 26.33 | 0.73 | 10.88 | 0.43 | 52.0 | 95 |
| FS9733DD B12B(S) | sleeve/ball | 12 | 0.55 | 6.60 | 2800 | 22.50 | 0.63 | 9.28 | 0.36 | 47.0 | |
| FS9733DD B12B(S) | sleeve/ball | 12 | 0.45 | 5.40 | 2400 | 18.35 | 0.51 | 7.75 | 0.30 | 41.0 | |
| FS9733DD B12B(S) | sleeve/ball | 12 | 0.35 | 4.20 | 2000 | 15.05 | 0.42 | 6.23 | 0.24 | 35.0 | |
| FS9733DD B24B(S) | sleeve/ball | 24 | 0.55 | 13.20 | 3200 | 26.33 | 0.73 | 10.88 | 0.43 | 52.0 | |
| FS9733DD B24B(S) | sleeve/ball | 24 | 0.40 | 9.60 | 2800 | 22.50 | 0.63 | 9.28 | 0.36 | 47.0 | |
| FS9733DD B24B(S) | sleeve/ball | 24 | 0.35 | 8.40 | 2400 | 18.35 | 0.51 | 7.75 | 0.30 | 41.0 | |
| FS9733DD B24B(S) | sleeve/ball | 24 | 0.25 | 6.00 | 2000 | 15.05 | 0.42 | 6.23 | 0.24 | 35.0 | |