

FS2589 Size:254*89mm AC Axial Fan

Frame:Aluminum Alloy

Impeller:PBT+30%GF

Lead Wire:AWG#20 UL1015(Optional)

Motor:Shaded Pole Induction Motor

Insulation:CLASS B



Specification:

Model	Bearing	Rated voltage(v)	Frequency (HZ)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air pressure		Noise (dB)	Weight(g)
FS-2589 H23	ball	230	50/60	0.60/0.70	100/130	2600/3000	21/ 32	0.83/0.91	65/62	1900
FS-2589 M23	ball	230		0.35/0.45	65/80	2300/2300	17.5/19	0.69/0.75	59/59	
FS-2589 L23	ball	230		0.20/0.25	31/33	1400/1650	8.9/12	0.35/0.47	55/52	
FS-2589 H12	ball	120		1.0/1.5	100/130	2600/3000	21/ 32	0.83/0.91	65/62	
FS-2589 M12	ball	120		0.75/0.90	65/80	2300/2300	17.5/19	0.69/0.75	59/59	
FS-2589 L12	ball	120		0.28/0.30	31/33	1400/1650	8.9/12	0.35/0.47	55/52	
FS-2589 H38	ball	380		0.30/0.35	100/130	2600/3000	21/ 32	0.83/0.91	65/62	
FS-2589 M38	ball	380		0.35/0.45	65/80	2300/2300	17.5/19	0.69/0.75	59/59	