

FS9225 Size:92*92*25mm DC Axial Fan



Frame:Aluminum Alloy
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#24 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow		Air pressure		Noise (dB)	Weight(g)
						(CFM)	(m ³ /min)				
FS9225D DA12B(S)	sleeve/ball	12	0.50	6.00	3200	85.55	2.39	4.81	0.18	50.0	75
FS9225H DA12B(S)	sleeve/ball	12	0.25	3.00	2800	65.01	1.82	3.83	0.15	40.0	
FS9225M DA12B(S)	sleeve/ball	12	0.20	2.40	2500	46.30	1.29	3.05	0.12	30.0	
FS9225L DA12B(S)	sleeve/ball	12	0.16	1.92	2000	38.80	1.08	2.18	0.08	23.0	

Shenzhen Fu Sheng Electric Co.,Ltd.
No.1,Block3,Hongchang,Shunchang Street,Pinghu,Longgang District,Shenzhen China
Tel:0755-8466-0060 Mobile:+86 13662256009

FS9225D DA24B(S)	sleeve/ball	24	0.35	8.40	3200	85.55	2.39	4.81	0.18	50.0
FS9225H DA24B(S)	sleeve/ball	24	0.22	5.28	2800	65.01	1.82	3.83	0.15	40.0
FS9225M DA24B(S)	sleeve/ball	24	0.18	4.32	2500	46.30	1.29	3.05	0.12	30.0
FS9225L DA24B(S)	sleeve/ball	24	0.15	3.80	2000	38.80	1.08	2.18	0.08	23.0
FS9225H DA48B(S)	sleeve/ball	48	0.13	6.24	3200	65.01	1.82	3.83	0.15	40.0
FS9225M DA48B(S)	sleeve/ball	48	0.07	3.36	3000	46.30	1.29	3.05	0.12	30.0