

Membrane filter press Features:

1. Can withstand strong acid, strong alkali, high temperature 100 degrees, high pressure, etc.
2. After pressing, some material moisture can reach as low as 20-30%, which is convenient for subsequent processing.
3. Can operate automatically, computer remote control, labor saving.

The structure of membrane filter plate:

Membrane is form by different material. The diaphragm is made of special rubber compounding formula, the core plate material is improved PP, Then the finished membrane plate is processed by numerical control.

Specification	Filter area (m2)	Filter plate size (mm)	Filter cake thickness (mm)	Filter chamber volume (L)	Filter plate number (pcs)	Filtrating pressure (Mpa)	Motor power (kw)	Weight (kg)
BYZ30/870-30U	30	870*870	30	427	23	0.6	2.2	3046
BYZ40/870-30U	40			534	29			3593
BYZ50/870-30U	50			748	38			4057
BYZ60/870-30U	60			902	46			4597
BYZ70/870-30U	70			1056	54			5136
BYZ80/870-30U	80			1210	62			5636
BYZ50/1000-30U	50	1000*1000		752	28	0.6	4.0	4128
BYZ60/1000-30U	60			908	34			4636
BYZ70/1000-30U	70			1063	40			5143
BYZ80/1000-30U	80			1219	46			5651
BYZ100/1000-30U	100			1505	57			6628
BYZ120/1000-30U	120			1816	69			764



Abby Song

	+86-18701854523		+86-18701854523
	abbasong249		+86-18701854523
	+86-18701854523		sales1@filterpressure.com