



specifications

1. Material:

- 1-1. Molded portion: LCP resin (ul94-0).
- 1-2. Contact and post: copper alloy.

2. Surface treatment:

- 2-1. Terminal portion; base; Ni plating surface; Au plating (except the terminal tips); exposed nickel portions.
- 2-2. Metal clips: base; Ni plating surface; Au flash plating (except the terminal tips) or base; Ni plating surface; Sn flash plating (except the terminal tips)

3. Characteristics:

- 3-1. Rated voltage: 60V AC/DC
- 3-2. Rated current: 0.3A/contact (Max. 5A at total contact)
- 3-3. Insulation resistance: Min. 1000MΩ (initial)
- 3-4. Breakdown voltage: 150V AC for 1 min.
- 3-5. Saltwater spray resistance (header and socket mated): 24 hours, insulact resistance max. 90mΩ.
- 3-6. Contact resistance: Max. 90mΩ.
- 3-7. Ambient temperature: -55°C ~ +85°C.
- 3-8. Storage temperature: -55°C ~ +88°C (product only); -40°C ~ +50°C (emboss packing).
- 3-9. Composite insertion force: Max. 0.918N/contacts X contacts (initial).
- 3-10. Composite removal force: Min. 0.165N/contacts X contacts.
- 3-11. Post holding force: Min. 0.49N/contacts.
- 3-12. Insertion and removal life: 50 times.

Ordering Code:

BB0.4 - M - 0.8 - X - X - X - 02
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series NO:
0.4mm Board to Board connector
- ② M: Male F: Female
- ③ mating Height:
0.8=0.80mm
- ④ NO. of contacts:
see table
For example
24:24poles
- ⑤ Contact Plating
G0: Gold flash
G1: 3u" Gold
G2: 5u" Gold
G3: 10u" Gold
G4: 15u" Gold
G5: 30u" Gold
SN: Tin
- ⑥ Packing
T: Tube A: Tray
B: Bag U: Tube+CAP
R: tape&Reel
W: tape&Reel+CAP
- ⑦ serial number: 02

TABLE:

70	15.80	15.20	13.60
50	11.80	11.20	9.60
40	9.80	9.20	7.60
34	8.60	8.00	6.40
30	7.80	7.20	5.60
24	6.60	6.00	4.40
10	3.80	3.20	1.60
NUMBER OF CONTACTS	A	B	C

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW Mo Guo Xuan DATE 12/11/2018
 CHECK BobYang DATE 12/11/2018

Antenk ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail: sales@antenk.com

TITLE: 0.4mm Board to Board connector, male, mating Height=0.80mm

DRAWING NO: BB0.4M-0.8XXX02

PRODUCT NO: BB0.4M-0.8XXX02



REV	DESCRIPTION	DATE
-----	-------------	------