

P. G. B EDGE
RECOMMENDED P. C. B LAYOUT

Material:

Housing: Temperature Thermoplastics, PBT+G.F UL 94V-0

Contact: Brass or Bronze

Shell: Steel Nickel Plating All Area

Electrical Characteristics:

Current Rating: 5A

Contact Resistance: 30 milliohms Max

Withstanding Voltage: 1000V AC For 1 Minute

Insulation Resistance: 5000 Megohms Min

Operating Temperature: -55° C to +105° C

Ordering Code:

HDDR01- FF - X - X - X - B - S
 ① ② ③ ④ ⑤ ⑥ ⑦

① Dual Port Angle DIP

② Contact Type:
FF:Female TO Female

③ Contact NO. :
P1=15 TO 15 P2=26 TO 26
P3=44 TO 44 P4=62 TO 62

④ Row Spacing:
A: Dim.E=15.88mm
B: Dim.E=19.05mm
C: Dim.E=22.86mm

⑤ Other Option:
C:Riveted ground hooks
with #4-40UNC Open
S:Riveted ground hooks
Pre-Loaded #4-40UNC Hex screws

⑥ Color Code:

B:Black L:Blue
W:White G:Grey

⑦ Contact Plating

S: Selective Gold
S1:Selective 3u" Gold
S2:Selective 5u" Gold
S3:Selective 10u" Gold
S4:Selective 15u" Gold
S5:Selective30u" Gold
G0: Gold flash
G1: 3u" Gold over
G2: 5u" Gold over
G3: 10u" Gold over
G4: 15u" Gold over
G5: 30u" Gold over


No.of Contacts	Dim.A	Dim.B	Dim.C	Dim.D	Dim.E	Dim.F	Dim.G	Dim.H
15	30.81	24.99		16.33	2.29			0.25
26	39.14	33.32		24.66	2.29	15.88	28.40	0.51
44	53.04	47.04		38.38	2.29			0.51
62	69.32	63.50		54.84	2.41	19.08	31.60	0.58

Unless Otherwise specified tolerance
 X. ±0.35 X.XX:±0.20
 X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm

DRAW Lv Xun Hua DATE 21/03/2019

CHECK BobYang DATE 21/03/2019



Antenk ANTEK ELECTRONICS CO.,LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE: D-SUB P.C.B High density Dual Port Right Angle Female TO Female(stamped Pin)

DRAWING NO: HDDR01-FFXXXXX

PRODUCT NO: HDDR01-FFXXXXX

REV

DESCRIPTION

DATE

1

2

3

4

5

6

7

8