

SPECIFICATION

Standard(参考标准): UL IEC
 Voltage Rating(额定电压): 300V 450V
 Current Rating(额定电流): 10A 17.5A
 Wire range(使用线径): 22-16AWG 1.5mm²
 Withstanding voltage(耐电压): AC2000V/1Min
 Insulation resistance(绝缘电阻): 500MΩ/DC500V
 Temp Rang(温度范围): -40° C ~ +105° C
 Max Torque(最大锁紧力矩): 0.5Nm(4.5lb. in)
 Housing(塑件): PA66, UL94V-0
 Screw(螺丝): Steel, M3.0 Ni-Plated
 Terminal(端子): Brass.0.8t, Tin Plated
 Pitch(间距): 7.62mm
 Poles(极数): 2P-XXP

Ordering Code:


AT828 - 7.62 - XX - X - 02

Pitch: 7.62:7.62mm
 Poles: 02: 2 Contacts
 03: 3 Contacts

 22: 22 Contacts
 Insulator color: 02:Series number.
 A:Green B:Blue
 C:Black G:Gray
 O:Orange T:Transparent
 R:Red Y:Yellow
 W:White

Unless Otherwise specified tolerance
 X.±0.35 X.XX:±0.20
 X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm
 DRAW Wu Sai DATE 22/03/2018
 CHECK BobYang DATE 22/03/2018



Antenk® ANTENK ELECTRONICS
 www.antenk.com
 E-mail:sales@antenk.com

TITLE:
 Barrier Terminal Block Pitch:7.62mm

DRAWING NO: AT828-7.62XXX-02

PRODUCT NO: AT828-7.62XXX-02

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		