

HSF







SPECIFICATION

Current Rating: 7 Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65°C to +125°C
 Contact Material: Brass
 Insulator Material: LCP,UL 94V-0 Black

Ordering Code:

PHFS02 - X - X - S - A-C-B - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No:
- ② No. of Contacts
01 To 40
- ③ Contact Plating:
G0:Gold flash S0:Selective
G1:3U" Gold S1:Selective 3u"
G2:5u" Gold S2:Selective 5u"
G3:10u" Gold S3:Selective 10u"
G4:15u" Gold S4:Selective 15u"
G5:30u" Gold S5:Selective 30u"
SN:Tin
- ④ Connector Type
S:Single
- ⑤ Pin Length:
A:0600=6.00mm
C:0800=8.00mm
B:0350=3.50mm
Please mark the desired length in the A/C/B
- ⑥ Insulator Material
B:PA6T
C:LCP
E:PA9T
- ⑦ Packing:
A:Tray
B:Bag
T:Tube
U:Tube+CAP
R:Tape&Reel
W:Tape&Reel+CAP



PCB LAYOUT

Standard IE P/N :


PHFS02-10-G0-S-0600-0800-0350-C-B

A	C	B	Unless Otherwise specified tolerance	
6.0	8.0	3.5	X. ±0.35	X.XX: ±0.20
			X.X: ±0.25	X.XXX: ±0.15
Optional		SCALE: As Shown	UNIT: mm	
DRAW		YG ZHONG	DATE 01/05/2016	
CHECK		BobYang	DATE 01/05/2016	

Antenk ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE:
3.96mm Pin Header Single Row Dual Plastic Straight Type

REV	Increase packing method and material	2016/10/25
	DESCRIPTION	DATE



DRAWING NO: PHFS02-XXS-0600-0800-0350-XX
 PRODUCT NO: PHFS02-XXS-0600-0800-0350-XX