



SECTION A-A

SPECIFICATION

Standard(参考标准): UL IEC  
 Voltage Rating(额定电压): 300V 450V  
 Current Rating(额定电流): 20A 32A  
 Wire range(使用线径): 22-12AWG 4.0mm<sup>2</sup>  
 Withstanding voltage(耐电压): AC2000V/1Min  
 Insulation resistance(绝缘电阻): 500MΩ/DC500V  
 Temp Rang(温度范围): -40° C ~ +105° C  
 Max Torque(最大锁紧力矩): 0.5Nm(4.5lb. in)  
 Housing(塑件): PA66, UL94V-0  
 Screw(螺丝): Steel, M3.0 Ni-Plated  
 Terminal(端子): Brass 0.8t, Tin Plated  
 Pitch(间距): 8.5mm  
 Poles(极数): 2P-24P

Ordering Code:

AT826 - 8.5 - XX - X - 01

Pitch: 8.5:8.5mm  
 Poles: 02: 2 Contacts  
 03: 3 Contacts  
 ... ..  
 22: 22 Contacts  
 Insulator color: 01:Series number.  
 A:Green B:Blue  
 C:Black G:Gray  
 O:Orange T:Transparent  
 R:Red Y:Yellow  
 W:White

Unless Otherwise specified tolerance  
 X.±0.35 X.XX:±0.20  
 X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm  
 DRAW: Wu Sai DATE: 22/03/2018  
 CHECK: Bob Yang DATE: 22/03/2018



 ANTENK ELECTRONICS  
 Http://www.antenk.com  
 E-mail:sales@antenk.com

TITLE:  
 Barrier Terminal Block Pitch:8.5mm

DRAWING NO: AT826-8.5XXX-01

PRODUCT NO: AT826-8.5XXX-01

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		