




HSF



SPECIFICATION


Current Rating: 1Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65°C to +125°C
 Contact Material: Brass
 Insulator Material: PA6T UL 94V-0 Black



Ordering Code:

FHCU01 - X - X - D - X - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦


- ① Series No:
- ② No.of Contacts: 02 To 100
- ③ Contact Plating: G0:Gold flash S0:Selective
 G1:3U" Gold S1:Selective 3u"
 G2:5u" Gold S2:Selective 5u"
 G3:10u" Gold S3:Selective 10u"
 G4:15u" Gold S4:Selective 15u"
 G5:30u" Gold S5:Selective 30u"
 SN: Tin
- ④ Connector Type: D: Dual
- ⑤ Plastic High: H: 4.3
 Please mark the desired length in the H
- ⑥ Insulator Material: B:PA6T
 C:LCP
 E:PA9T
- ⑦ Packing: A:Tray
 B:Bag
 T:Tube
 U:Tube+CAP
 R:Tape&Reel
 W:Tape&Reel+CAP



PCB LAYOUT

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW: YG ZHONG DATE: 01/05/2016
 CHECK: BobYang DATE: 01/05/2016



Antenk ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE:
 1.27mm Female Header Dual Row Straddle Type

DRAWING NO: FHCU01-XXDXXX
 PRODUCT NO: FHCU01-XXDXXX

REV	DESCRIPTION	DATE