PNEUMATIC ROLLER

SR30YT-3

Ready for super heavy-duty roadwork

Engine model: Shangchai SC7H180.1G3

Rated power: 132 kW/2000 rpm

Max. operating weight: 30.0 t

Product features

With a powerful, fuel-efficient Shangchai engine, international water pump and greater compacting power plus efficient coverage for asphalt projects, the SR30YT-3 delivers real roadwork power. A five-gear system ensures accurate water application, and the exterior design incorporates indented stairs to the cab to enhance operator safety.



SHANTUI VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:

No. 58, G327 Highway Jining City, Shandong, CHINA

TEL: +86-537-2909369 FAX: +86-537-2311219 EMAIL: trade@shantui.com


PNEUMATIC ROLLER SR30YT-3 Technical specifications:

Overall length: 5060 mm Minimum turning radius: 9000 mm
Overall width: 2486 mm Fuel capacity: 195 L

Overall height: 3359 mm

| | WEIGHT AND DIMENSIONS | Weights | Operating weight | 16150 kg | | |
|------------|------------------------|---------------------------|-----------------------------|--------------------------|------------------|--|
| | | | Metal ballast | 12100 kg | | |
| | | | Water ballast | 1950 kg | | |
| | | | Maximum working weight | 30000 kg | | |
| | | Compaction characteristic | Working width | 2355 mm | | |
| | | | Tire distance | 510 mm | | |
| | | | Ground pressure | 200~545 kPa | | |
| | | | Wheelbase | 3840 mm | | |
| | | | Front/rear tire overlap | 70 mm | | |
| | | | Front tire oscillation | ±50 mm | | |
| | | Tires | Number of tires, front/rear | Front: 4/rear: 5 | | |
| | | | Tire size | 13/80-20 | | |
| | | | *** | 01 | L : 00711400 400 | |
| ° Ç | ENGINE AND DRIVE TRAIN | Engine | Make & model | Shangchai SC7H180.1G3 | | |
| | | | Туре | Turbocharged | | |
| | | | Fuel | Diesel | | |
| | | | Cooling | Water | | |
| | | | Number of cylinders | 6 | | |
| | | | Rated power | 132 kW | | |
| | | | Rated speed | 2000 rpm | | |
| | | Drive train | Minimum ground clearance | 290 mm | | |
| | | | Maximum climbing ability | 20 % | | |
| | | | Forward/ Reverse speed | 1 | 0~8 km/h | |
| | | | | | 0~20 km/h | |
| | | | | | | |
| | CABIN & CONTROLS | Electrical system | DC, negative ground | 24 V | | |
| | | | Alternator | 28 V, 55 A | | |
| | | Brakes | Service brake | Caliper dry disc | | |
| | | | Parking brake | Spring-loaded/mechanical | | |
| | | Steering | Steering system | Hydraulic | | |
| | | | Steering method | Articulation | | |
| | | | Steering angle (Grad) | ±33° | | |
| | | | Steering radius | 8.5 m | | |
| | | | • | | | |

OVERALL DIMENSIONS





THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.