

SL30WN

National III emission standard.

- ▶ Engine model: Weichai WP6G125E201
- ▶ Rated power: 92 kW/2000 rpm
- ▶ Operating weight: 10.3 t

Product features

Another small offering in wheel loaders, the SL30WN still offers mid-range performance for its size. It has auto-lubrication in the bucket and arm joints. The sealed glass cabin offers a wide field of vision and a shock absorbing seat for greater driver comfort and safety.



shantui e-shop

SHANTUI

VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:
No. 58, G327 Highway
Jining City, Shandong, CHINA


TEL: +86-537-2909369
FAX: +86-537-2311219
EMAIL: trade@shantui.com


SL30WN


Technical specifications:


	Standard Arm	Extended Arm	Long Arm
Overall length	7043 mm	7170 mm	7290 mm
Overall width	2484 mm	2484 mm	2484 mm
Overall height	3235 mm	3235 mm	3235 mm


SL30WN

 GENERAL SPECIFICATIONS	Operating weight	10300 kg
	Related loading	3000 kg
	Bucket capacity	1.7 m ³
	Maximum lifting force	105 kN
	Static tipping load (full turn)	6000 kg
	Dumping height (Standard arm/Extended/Long)	2875/3057/3200 mm
	Dumping reach (Standard arm/Extended/Long)	955/906/886 mm

 ENGINE	Engine model	Weichai WP6G125E201
	Type	In-line, water-cooled, 4-cylinder, direct injection, turbocharged
	Rated power	92 kW
	Rated speed	2000 rpm
	Displacement	6.75 L
	Maximum torque	540 N·m
	Minimum fuel consumption	217 g/kW·h

 TRAVEL SPEED	Gear	1st	2nd	3rd	4th
	Forward	0~7 km/h	0~12 km/h	0~23 km/h	0~37 km/h
	Reverse	0~8.3 km/h	0~28 km/h	-	-

 AXLES AND FINAL DRIVES	DRIVE SYSTEM		Four-wheel drive
	Gradeability		30°
	Maximum traction		110 kN
	BRAKE SYSTEM:	Service brakes	Air-on-oil callper disc brakes
		Parking brake	Shoe brake on gearbox output shaft
	STEERING SYSTEM:	Type	Articulated type, full-hydraulic power steering
		Maximum steering angle	36° each direction
		The center of outside tire	5100 mm
		The center of outside bucket	5920 mm
	TIRES	Type	17.5-25 12PR
		Pattern level	L3
		Center distance of tires	1856 mm
Wheel base		2700 mm	

 HYDRAULIC SYSTEM	Hydraulic cycle time (rated load in bucket)	Lifting time/ Lifting, dumping and lowering	5.1/9.0 s

OVERALL DIMENSIONS

▶ THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

