

3W

260LM

170°

IP65

LifeSpan
50,000h

Volt: **AC110V/220V**



Features



- Sourced by high output 3030 LED, good color conformity and no spot.
- 99.99% gold thread, pure copper bracket coated with silver.
- SDCM≤5 each BIN.
- Special lens design, 170°beaming angle with even light.
- Overmoulded: anti-dusting, anti-moisture, waterproof, anti-shock.
- 50 pcs Max. in a series connection.
- CE, RoHS and UL certified.

Application




- Best for 8-15 cm depth single-sided light box at airports, metros, banks, buildings and shopping malls, etc.

Parameters


Items	Parameters
Part Number	ZX04QG1
CCT (K)	7000K
Beaming Angle (°)	170
CRI (Ra)	≥75
Luminous Flux (lm)	260
Voltage (V)	AC110V/220V
Power (W)	3
Driving Method	Inner Constant Current
Dimension (mm)	157*28*8.8
Weight (g)	51
Working Tem. (°C)	-25 ~ +60
Storage Tem. (°C)	-25 ~ +70
Protection Grade	IP65

Dimension

Unit:mm



Beaming Angle >




Reference Scheme >

Depth(mm)	Distance(mm)	Density(pcs/m ²)	Illumination(lux)
Dz=120	Dx=310 Dy=120	27	3000-3500
Dz=150	Dx=310 Dy=120	27	2800-3000
Dz=180	Dx=310 Dy=120	27	2500-2800
Dz=200	Dx=310 Dy=120	27	2300-2400
Dz=250	Dx=310 Dy=120	27	2000-2200


Remark:

- The transmittance of the advertising fabric was 32%.
- The above data is for reference only.




Wire Connection >


White&Red wire to positive
 White&Black wire to negative




Packing



50cs in a string



50pcs in a plastic tray



300 pcs in a carton

Packing Specification



- Packed in plastic tray.
- Packing information

Part Number	ZX04QG1
Carton Dimension(mm)	490*450*220
Trays per carton	6
Quantity per carton(pcs)	300
Net Weight(kg)	20.4(1±10%)
Gross Weight(kg)	21.6(1±10%)

Due to the packing manner difference, please subject to the original products in case of discrepancy found between the picture and actual product.

Warning



- Disassembling or modifying the product is forbidden.
- Installation with power on is forbidden.
- Any organic solvent chemical is forbidden.
- Acidic or alkaline adhesive is forbidden when install, neutral glass cement could be used for installation purpose, make it drying in open environment for four hours.
- Isolation and corrosion prevention on all wiring points and wire ends.
- Make sure the power wire is thick enough and ensure the voltage and connections are connected correctly before power on.
- This product should be used in a sign, do not expose it in opening site.
- Installation, maintaining should be done by professional staff.
- 50 pcs in a serial connection maximum.
- The power wire between power supply and module should be less than two meters to keep the same brightness on all parts.
- Initial location with 3M tape, then secure with screws.

Declaration



- Warranty: 5 years.
- In order to ensure the safety, the broken wires need to be replaced by the manufacturer or the service agent, or by the staff with the similar qualification.
- The given data in the specification was based on the laboratory testing, there may be discrepancy found in the actual products.
- The given drawings in the specification are only for reference, there may be discrepancy found in the actual products.
- The products are subject to change without prior notification.



RoHS

Company Address:

Rm. WS, 9F, LuBan Building, Hongli West Road, Futian District,
Shenzhen, China 518034

Factory Address:

No. B, Xinyongfeng Industrial Area, Yingrenshi Village, Shiyuan Town,
Bao'an District, Shenzhen, China 518000

TEL: +86-755-83544570

FAX: +86-755-83056229

Website: www.lbyled.com

E-mail: info@lbyled.com



LBY LED®
signs never been so easy