

DATESHEET DL65-12

Date	2016.6.15	Protection保护	
General Data		IP Rating IP指数	IP 20
Category分类	LED down light	Protection class 防护等级	III
Input voltage输入电压	DC12V	Environment 环境	
Article No.型号	DL-65-12	Operating temperature range 工作温度	-20 °C - +45 °C
Short description简述	LED down light	Working humidity 工作湿度	40 - 80%
Switch开关	Not applicable	Storage temperature range 储存温度	-40 °C - +100 °C
Energy efficiency class (Ec class) 能效等级	A+	Additional Information 附加信息	
Weighted energy consumption (Ec)加权能量消耗	NO	Nominal lifetime L70 使用寿命	NO
Light technical Data灯技术参数		Lamp survival factor at 6000 h 存活系数	NO
Colour temperature色温	4000±300K 6000±500K	Lumen Maintenance at 6000 h 流明保持	NO
Chromaticity binning of the LED色度装箱	NO	Number of switching cycles before failure 损坏前开关的循环次数	NO
Colour consistency颜色一致性	No	Starting time启动时间	NO
Wattage功率	3W±10%	Lamp warm-up time at 95 % luminous flux 95%流明时的预热时间	NO
Number of LEDs灯珠数量	24PCS	Premature failure rate 过早故障率	NO
Type of LED灯珠类型	SMD2835	Lamp power factor (PF) for lamps with integrated control gear 灯功率因数(PF)灯与综合控制装置	Not applicable
Total luminous flux流明	210lm±10%	Approvals and Certificates 认证	
Efficacy效率	≥65lm/W	RoHS	Yes
Colour Rendering Index (CRI)显色指数	≥80	REACH	Yes
SCDM	≤5 step	Certificates, Approvals, Test-Symbols 认证、检测	
Viewing angle光照角度	120°	Detailed function description 详细功能描述	Not applicable
Dimmable可控制的	NO	Warranty 保证期	3 years
RGB	No	Packing 包装	
Mechanical Data 机械参数		MOQ 起订量	
Length长		outer carton 外箱	39*42*17cm 100PCS
Width宽		inner carton 内箱	Not applicable
Height高	12mm	inner box 内盒	75*75*40mm 1pcs
Diameter直径	∅ 65mm	outer polybag 外包装袋	Not applicable
Drill dimension 钻孔尺寸	∅ 55-∅ 57mm	inner polybag 内包装袋	Not applicable
Weight per pcs.单件重量		palet 托盘	
Housing main materials外壳主要材料	SPCC拉伸铁	sales price 售价	
Finish表面处理	镀铬		
Packing assessorries包装中的配件	N/A		
Mounting安装	嵌入安装		
Cable length电缆线长	2468 Black 2M±150MM		