

		NO	P3.91	P4.81	P5.95
Module	Pixel Pitch(mm)	3.91mm	4.81mm	5.95mm	
	Module Size(mm)	250*250mm	250*250mm	250*250mm	
	Module Resolution(pixel)	64*64	52*52	84*84	
	LED Type	SMD1921	SMD2727	SMD2727	
	Scan Mode	1/16scan	1/13scan	1/7scan	
	Application scene	Outdoor	Outdoor	Outdoor	
Cabinet	Cabinet Size(mm)	500×500mm/500×1000mm	500×500mm/500×1000mm	500×500mm/500×1000mm	
	Cabinet Resolution(pixel)	128*128/128*256	104*104/104*208	168*168/168*336	
	Material	AL	AL	AL	
	Cabinet Weight(KG)	8kg/13kg	8kg/13kg	8kg/13kg	
	Pixel Density	62500	43264	28224	
Display	Brightness	5500cd/ m <sup>2</sup>	4500cd/ m <sup>2</sup>	≥4500cd/ m <sup>2</sup>	
	Refresh Rate(HZ)	≥3840	≥3840	≥1920	
	Gray level	16bit	16bit	16bit	
	Avg.Power Consumption	250W/ m <sup>2</sup>	700W/ m <sup>2</sup>	500W/ m <sup>2</sup>	
	Max.Power Consumption	750W/ m <sup>2</sup>	1400W/ m <sup>2</sup>	800W/ m <sup>2</sup>	
	Viewing Angle	H:140° , V:140°	H:140° , V:140°	H:140° , V:140°	
	Service Access	Full front access	Full front access	Full front access	
	Operating Temp/Humidity	- 30°C ~ 60°C			
	Storage Temp/Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH	
	IP Grade	IP65	IP65	IP65	
	Best viewing distance	4-60m	5-50m	6.5-35m	