

		NO	P1.5	P1.6	P1.83	P2
Module	Pixel Pitch(mm)		1.538mm	1.66mm	1.839mm	2mm
	Module Size(mm)		320×160mm	320×160mm	320×160mm	320×160mm
	Module Resolution(pixel)		208*104	192*96	174*87	160*80
	LED Type		SMD1010	SMD1010	SMD1515	SMD1515
	Scan Mode		1/26S	1/32S	1/29S	1/20S
Cabinet	Cabinet Size(mm)		640×480mm	640×480mm	640×480mm	640×480mm
	Cabinet Resolution(pixel)		416*312	384*288	348*261	320*240
	Material		Die-casting	Die-casting	Die-casting	Die-casting
	Cabinet Weight(KG)		8	8	8	9
	Pixel Density		422500	360000	295664	250000
Display	Brightness		500cd/ m ²	500cd/ m ²	1000cd/ m ²	500cd/ m ²
	Refresh Rate(HZ)		≥3840	≥3840	≥3840	≥3840
	Gray level		16bit	16bit	16bit	16bit
	Avg.Power Consumption		600W/ m ²	600W/ m ²	400W/ m ²	400W/ m ²
	Max.Power Consumption		1200W/ m ²	1200W/ m ²	800W/ m ²	1000W/ m ²
	Viewing Angle		H:160° , V:160°	H:160° , V:160°	H:160° , V:160°	H:140° , V:130°
	Service Access		Full front access	Full front access	Full front access	Full front access
	Operating Temp/Humidity		-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C
	Storage Temp/Humidity		10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	IP Grade		IP65	IP65	IP65	IP65
Best viewing distance		1-20M	1-25M	1-28M	2-20M	

	NO	P2.5	P3	P3.07
Module	Pixel Pitch(mm)	2.5mm	3mm	3.076mm
	Module Size(mm)	320×160mm	320×160mm	320×160mm
	Module Resolution(pixel)	128*64	64*64	104*52
	LED Type	SMD2020	SMD2121	SMD1515
	Scan Mode	1/32S	1/32S	1/26S
Cabinet	Cabinet Size(mm)	640×480mm	640×480mm	640×480mm
	Cabinet Resolution(pixel)	256*192	128*192	208*156
	Material	Die-casting	Die-casting	Die-casting
	Cabinet Weight(KG)	9	9.5	9.5
	Pixel Density	160000	111111	105625
Display	Brightness	600cd/ m ²	1000cd/ m ²	1000cd/ m ²
	Refresh Rate(HZ)	≥3840	≥3840	≥3840
	Gray level	16bit	16bit	16bit
	Avg.Power Consumption	600W/ m ²	600W/ m ²	600W/ m ²
	Max.Power Consumption	1200W/ m ²	1300W/ m ²	1300W/ m ²
	Viewing Angle	H:140° , V:130°	H:140° , V:130°	H:140° , V:130°
	Service Access	Full front access	Full front access	Full front access
	Operating Temp/Humidity	-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C
	Storage Temp/Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	IP Grade	IP65	IP65	IP65
Best viewing distance	2-30M	3-30M	3-30M	