

NO		P1.5	P1.6	P1.875	P1.9
Module	Pixel Pitch(mm)	1.56mm	1.66mm	1.875	1.923
	Module Size(mm)	200×150mm	200×150mm	240×240mm	200×150mm
	Module Resolution(pixel)	128*96	120*90	128*128	104*78
	LED Type	SMD1010	SMD1010	SMD1515	SMD1515
	Scan Mode	1/32	1/30	1/32	1/32
Cabinet	Cabinet Size(mm)	400×300×55mm	400×300×55mm	480×480×75mm	400×300×55mm
	Cabinet Resolution(pixel)	256*192	240*180	256*256	208*156
	Material	Die-casting	Die-casting	Die-casting	Die-casting
	Cabinet Weight(KG)	3.5	3.5	5.5	3.5
	Pixel Density	409800	360000	284000	270400
Display	Brightness	200cd~800cd/ m <sup>2</sup>	200cd~500cd/ m <sup>2</sup>	200cd~600cd/ m <sup>2</sup>	200cd~800cd/ m <sup>2</sup>
	Refresh Rate(HZ)	≥3840	≥3840	≥3840	≥3840
	Gray level	18bit	18bit	16bit	18bit
	Avg.Power Consumption	100W/ m <sup>2</sup> ~ 300W/ m <sup>2</sup>	100W/ m <sup>2</sup> ~ 300W/ m <sup>2</sup>	100W/ m <sup>2</sup> ~ 300W/ m <sup>2</sup>	100W/ m <sup>2</sup> ~ 300W/ m <sup>2</sup>
	Max.Power Consumption	600W/ m <sup>2</sup>	550W/ m <sup>2</sup>	500W/ m <sup>2</sup>	500W/ m <sup>2</sup>
	Viewing Angle	H:160° , V:160°	H:160° , V:160°	H:160° , V:160°	H:160° , V:160°
	Service Access	Full front access	Full front access	Full front access	Full front access
	Operating Temp/Humidity	-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C	-10°C ~ 60°C
	Storage Temp/Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	Frame rate	60fps/120fps	60fps/120fps	60fps/120fps	60fps/120fps
	Brightness level	Manually/Auto/Programmable			