

NO		P1.9	p2.5	P3.9	P4
Module	Pixel Pitch(mm)	1.94mm	2.5mm	3.91mm	4mm
	Module Size(mm)	210*280mm	210*280mm	250*250mm	256*128mm
	Module Resolution(pixel)	108*144	84*112	64*64	64*32
	LED Type	SMD1010	SMD2020	SMD1921	SMD1921
	Scan Mode	1/32scan	1/32scan	1/16scan	1/8scan
	Application scene	Indoor	Indoor	Outdoor	Outdoor
Cabinet	Cabinet Size(mm)	1902×572×35mm	1902×572×35mm	1150×2300mm	1792×896×120mm
	Cabinet Resolution(pixel)	972*288	756*224	256*576	448*224
	Material	AL	AL	AL	Iron
	Cabinet Weight(KG)	32	32	180	150
	Pixel Density	279936	169344	65536	62500
Display	Brightness	800cd/ m <sup>2</sup>	800cd/ m <sup>2</sup>	≥4500cd/ m <sup>2</sup>	≥4500cd/ m <sup>2</sup>
	Refresh Rate(HZ)	≥2880	≥2880	≥1920	≥1920
	Gray level	16bit	16bit	16bit	16bit
	Avg.Power Consumption	250W/ m <sup>2</sup>	200W/ m <sup>2</sup>	250W/ m <sup>2</sup>	1000W/ m <sup>2</sup>
	Max.Power Consumption	750W/ m <sup>2</sup>	600W/ m <sup>2</sup>	750W/ m <sup>2</sup>	2000W/ m <sup>2</sup>
	Viewing Angle	H:160° , V:160°	H:160° , V:160°	H:160° , V:160°	H:160° , V:160°
	Service Access	Full front access	Full front access	Front and Back access	Back access
	Operating Temp/Humidity	- 10°C ~ 40°C	- 10°C ~ 40°C	- 30°C ~ 60°C	- 30°C ~ 60°C
	Storage Temp/Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	IP Grade	IP65	IP65	IP65	IP65
Best viewing distance	2-20m	2-20m	4-60m	4-40m	