



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: elin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, +86-18339818406

Multifunctional Antiwear Hydraulic Oil Additive Package

Product Introduction

T5008 is formulated with antioxidant, anti-corrosion agent and anti-wear agent, etc. The hydraulic oil blended with T5008 possesses excellent antioxidant, anti-rusting and antiwear properties, it can longer the service life of oil and engine, inhibit the formation of varnish.

Recommended Treat Rate (wt%):

0.65-0.80%

Net Weight:

200 Kgs/Drum

Storage and Transportation:

Non-dangerous goods, store in dry, cool ventilated area.

Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Yellow transparent liquid	Visual
Kinematic Viscosity, 100°C, mm ² /s	Report	ASTMD445
Flash Point, °C	>110	ASTMD92
Sulfur, wt%	10-15	ASTMD5185
Phosphorus, wt%	5.5-7.5	ASTMD5185
Zinc, wt%	7.0-8.5	ASTMD5185