



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: eilin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, +86-18339818406

HDEO Vehicle Diesel Engine Oil Additive Package

●Product Introduction

T32065 is the mainstream diesel engine oil additive package product. It provide high quality and stable performance for heavy duty diesel engine. The product contains optimized combination of dispersant, antioxidant, excellent detergent, and has excellent wear resistance, effective protection of the engine and prolong the oil service life.

●Recommended Dosage

API Performance Level	Treating Rate (mass%)
CI-4, ACEA E7	12.0%
CH-4	10.0%
SN	7.8% + 1.2% Booster
SM	7.8% + 0.6% Booster

●Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Red-brown viscous liquid	Visual Inspection
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T 265
Flash Point (COC),°C	> 110	GB/T 3536
Total Base Number, mgKOH/g	110	SH/T 0251
N Content, m%	0.75	ASTM D5185 (ICP)
Zn Content, m%	1.20	ASTM D5185 (ICP)
Ca Content, m%	3.75	ASTM D5185 (ICP)
P Content, m%	1.0	ASTM D5185 (ICP)

●Product Storage/Handling/Transportation/Package

The storage temperature should not exceed 50°C, the loading/unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection, use, etc. It is same as normal petroleum product, with no special protection. Product package: The product is packed with 200 liters iron drum or according to user's requirement. Specific weight of delivery is subject to the actual filling weight.