# BT77501A Quenching Oil Additives

#### •Description:

BT77501Aiscompoundedbyhighqualityantioxidant,coolingaccelerant,brighteningagent,anti-rustag ent,corrosioninhibitor,etc,Quenchingoilscompoundedbyithavequalifiedtemperaturecharacteristics,t imecharacteristics,long-term performance and just little deposition,It has excellent quenching ability to increase the cooling speed significantly,It also has the ability to keep the metal surface brightening.

## •Recommended Dosage:

| Performance Level               | Dosage(W%) |  |
|---------------------------------|------------|--|
| Rapid Brightening quenching oil | 4%         |  |
| Rapid quenching oil             | 5%         |  |
| Overspeed quenching oil         | 6.50%      |  |

#### • Characteristics:

| Item                             | Typical Value            | Test Method       |
|----------------------------------|--------------------------|-------------------|
| Appearance                       | Brown Transparent Liquid | Visual Inspection |
| Kinematic Viscosity,100°C, mm2/s | Report                   | ASTMD445          |
| Flash Point(COC), °C             | >110                     | ASTMD92           |

## Packing And Storage

It is packed in 200 liter standard metal drums, 180kg per drum

The storage transport and production should meet the requirements of SH/T0164

The maximum temperature should not exceed  $75^{\circ}$ C, for long-term storage, the maximum temperature should not exceed  $45^{\circ}$ C, the product is not flammble, explosive, and corrosive, its safety cause, environment protection and usage may refer to the general procedures for the common petroleum products.