ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Chorus Email: sales@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 13783582233

Industrial Screw Air Compressor Oil Additive Package T66063

Product Introduction

T66063 is formulated with different kinds of Antiwear EP Additive, High Temperature Antioxidant, Rust Preventative Anti-rust Additive, etc. It has excellent anti-wear, high-temp anti-oxidation and antirust properties. It can also inhibits the formation of carbon sludge and has outstanding demulsibility. The oil blended with T66063 can meet the standard of foreign similar products.

Recommended Treat Rate (wt%):

L-DAA: 0.30-0.60% L-DAB: 0.60-0.80% L-DAG: 1.15%

Net Weight: 170 Kgs/Drum

Storage and Transportation: Non-dangerous goods, store in dry, cool ventilated area.

Product Quality Characteristics & Test Method

Troduct Quality Characteristics & Test Method		
Item	Typical Value	Test Method
Appearance	Yellow transparent liquid	Visual
Kinematic Viscosity, 100°C, mm²/s	Report	ASTMD445
Flash Point, ℃	>110	ASTMD92