



Chorus

ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: sales@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 13783582233

Industrial Screw Air Compressor Oil Additive Package T6036

- **Product Introduction**

T6036 Air Compressor Oil Additive Package is mainly composed of a variety of antioxidants, antirust agents, antiwear agents, extreme pressure agents and other additives. It has excellent antiwear, high temperature antioxidant, antirust and good emulsifying properties.

- **Scope of application:**

It can adjust N32, N46, N68 and other viscous compressor oils. The quality of oil meets the requirement of GB5940-86 standard.

Recommended dosage: L-DAA: 0.6%; L-DAB: 0.8%; Rotary screw compressor oil: 1.5%; T6036 of 1.5% in Class III 250N base oil, Rotary oxygen bomb more than 1400 minutes.

- **Technical conditions**

Item	Quality index	Test Method
Appearance	Yellow transparent liquid	Visual
Density(20°C)/(kg/m ³)	Measured	GB/ T1884
KV(100°C)/(m ² /s)	Measured	GB/ T265
Flash Point(Opening) °C	≥ 160	GB/ T3536
Nitrogen content/%	≥ 1.8	SH/ T0224
Water content/%	≤ 0.3	GB/ T260

- **Cautions for storage, transportation and use**

Packing, marking, transportation, storage and delivery acceptance shall be carried out according to SH/T0164. 200L galvanized iron drum packaging. Storage should be in dry, ventilated warehouse below 45 °C, blending temperature should not exceed 75°C. This product is non-flammable, non-explosive and non-corrosive. Preventive measures of general concentrated chemicals should be implemented in the process of feeding and using to avoid contact with skin. Once in contact, rinse with soapy water.