



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: eilin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, +86-18339818406

Screw Air Compressor Lubricant Oil Additive Package

●Contact Information:

Sales Manager: Eilin

Email:eilin@cn-lubricantadditive.com

Whatsapp/Line: +8618339818406

Product Introduction

T66063 is formulated with different kinds of Antiwear EP Additive, High Temperature Antioxidant, Rust Preventative Anti-rust Additive, etc. It has excellent anti-wear, high-temp anti-oxidation and antirust properties. It can also inhibits the formation of carbon sludge and has outstanding demulsibility. The oil blended with T66063 can meet the standard of foreign similar products.

Recommended Treat Rate (wt%):

L-DAA: 0.30-0.60%

L-DAB: 0.60-0.80%

L-DAG: 1.15%

Net Weight: 170 Kgs/Drum

Storage and Transportation:Non-dangerous goods, store in dry, cool ventilated area.

Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Yellow transparent liquid	Visual
Kinematic Viscosity, 100°C, mm ² /s	Report	ASTMD445
Flash Point, °C	> 110	ASTMD92