

Chorus Email: eilin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 18339818406

Lubricant Antifoam Additives for Hydraulic Lubricant Oil

•Contact Information:

Sales Manager: Eilin

Email:eilin@cn-lubricantadditive.com

Whatsapp/Line: +8618339818406

• Product Introduction

This product adopts patented technology, it has a little effect on air release, and have effective anti-foaming ability for special foaming substances. This kind of additive have good oil solubility, easy to use, no need to dilute, and can added to oil products directly.

•Reference Dose: 0.01%-0.1%

Physicochemical Properties Typical Value

Density(20°C) kg/m³ 780 Flash Point 70 Machine Miscellaneous, % (m/m) 0/01

Anti-foam (24°C, 500SN) ml/ml 25/0

Transparent liquid Appearance

• Product Storage/Handling/Transportation/Package

This kind of product is non-flammable, non-explosive and non-corrosive. Packaging, labeling, transportation, storage and acceptance of delivery should carry out by SH0164 Product packaging: 150kg metal drum or according to user requirements packaging.

Remarks: If it touches the skin carelessly, you can wash through detergent and water.