



Q5801 Specification

Black mark detection	Support clearance label
print density	384 points / lines
Printed Line Width	24 Chinese/Line 48 English/Line Or 36 Chinese/Line 72 English/Line
Printing speed	70MM/S
Printing Content	English, numbers, various symbols, characters, pictures, 1D and 2D code printing ,different languages
Support System	Android,iOS,(Win9X/Win ME/Win2000/WinNT/WinXP/WinVista/Win7, Win8/Linux)
Instruction Set	ESC/POS Compatible Instruction Set
Build-in Font	ASCII Font library(12*24 8*16) GBK(24*24 16*16) (32*32 , 48*48)
Paper type	thermal paper /thermal label paper /label paper
Paper diameter	Maximum Φ39mm

Application Environment

Storage temperature	-20° to 70°C
Humidity	0 ~ 95% (Non Condensing)
Error warning	Paper deficiency/Paper barn door/Low electricity
Print width	Paper Width: 58MM Effective Printing Width : 48MM
Battery	Detachable 9V1.5A 1400mAh high performance lithium battery
Power adapter	Input AC 110-240V , output DC 9V/1.5A
Size(LxWxD)	120*100*50.5MM
Weight	265g

Communication

Bluetooth	Bluetooth 2.0/4.0
USB	USB2.0
Processor	M3 32 bit processor
Flash	2048Kb RAM
Printing method	Line type thermal printing

Accessories

SHENZHEN QUNSUO TECHNOLOGY CO., LTD www.qsprinter.com



Shenzhen Qunsuo Technology Co., LTD

Address: 4F C Building ,Fuxinlin Industrail Park ,Xixiang ,Bao' an,Shenzhen ,China

Web:www.qsprinter.com

Tel :0086-0755-61153535