

PDA401 Specification Sheet

System Configuration

Processor	ARM Cortex A53 Quad-core 64bits 1.3GHz
O.S	Android6.0
Memory	16GB ROM+2GB RAM
Ex-Storage	Micro SD (Up to 64GB)
Display	4.0inch IPS 480x800 High Resolution
Camera	AF 5.0M(8.0M) Pixels with LED flash light
Touch Panel	Industrial-grade capacitive touch panel
Keypad	23 anti-wear, within the light waterproof industrial keyboard
Notification	Vibrator/LED/Speaker
Battery	3.7v 4000mAh rechargeable lithium polymer battery
Audio	Built-in microphone/Speaker
Sensor	G-sensor
Interface	Micro USB/Serial Port(TTL)

Structural Parameters

Dimensions(L xW xD)	162mm×70mm×31mm
Weight	345g(battery included)

Communication Transmission

Mobile Network	3G : WCDMA:850/900/1900/2100MHz CDMA/EVDO 800MHz GSM: 850/900/1800/1900MHz 4G : LTE-FDD:B1/B3/B7/B8/B28 LTE-TDD:B38/B39/B40/B41
Wi-Fi	IEEE 802.11 b/g/n
Bluetooth	Bluetooth 4.0
GPS	Supporting GPS/AGPS

NFC/HF RFID

Protocol	ISO/IEC 14443A/B,ISO15693
Frequency	13.56MHz
NFC type	Type1-4Tag/Mifare/Felica

PSAM

PSAM	ISO/IEC 7816 1-4
------	------------------

Operating Environment

Develop Tools	Android SDK + JDK + Eclipse
P-Language	Java
Operating Temp.	-10°~ 50°C
Storage Temp.	-20°~ 70°C
Humidity	0 ~ 95% (non-condensing)
Sealing	IP65

1D Laser Scanner

Speed	100 lines/sec
Scan Angle	±50°
Identification accuracy	≥4mil

Decoding Type	UPC-A ,UPC-E ,UPC-E1 ,EAN-13 ,EAN-8 ,ISBN/ISSN ,Code 39 ,code39 (ASCII full) , Interleaved 2 of 5 , Industrial 2 of 5,Matrix 25,Codebar(NW7) , Code 128 , UCC/EAN 128 , ISBT128 , code 93 , MSI/Plessey , UK/Plessey , China post , GS1 Data Bar
---------------	--

2D Image Scanner

Method	CMOS Image
Scan Speed	60scans/sec
Scan Angle	360 ° angle, Elevation angle ± 55 °, Eeflection angle ± 55 °
Identification accuracy	2D≥7.5mil , 1D≥5mil
Decoding Type	QR Code, Data Matrix, PDF417 , UPC-A, UPC-E, EAN-8, EAN-13, ISBN, Code 128, GS1 128, ISBT 128, Code 39, Code93,Code 11, Interleaved 2 of 5, Industrial 2 of 5,Matrix 25, Standard 25, Coda bar, MSI/MSI PLESSEY, GS1 Data Bar
DPM	Support DPM scanner (optional)

UHF RFID(Optional)

Frequency	902Mhz-928Mhz、865MHz-868MHz(optional)
Protocol	EPC global UHF Class 1 Gen 2/ISO 18000-6C
Capture Range	1-2m
Output Power	18-26dBm

Accessories

