

ACTMIX ETU-75GN F140

Accelerator ETU (NA-22)

C

Т V Ε

M

A т Ε R

R

В

A

Т

C

Н

Ethylene thiourea

 $C_3H_6N_2S$ M.W.: 102.16 CAS: 96-45-7

EINECS: 202-506-9

PROPERTIES:

ETU can accelerate vulcanization rate of CR and has high scorching safety. It is APPLICATIONS: an activator and secondary accelerator for CR, CSM CPE products. low-sulfur or non-sulfur vulcanization of other dienes rubber. It can improves heat-proof aging and physical mechanics properties of vulcanizates. Generally it Ash content: Max 0.3% causes no blooming appearance.

DOSAGE:

0.1-2phr usually.

TYPICAL VALUES:

Melting point: Min 192°C

Purity: Min 98%

Volatile content: Max 0.3%

63µm sieve residue: Max 0.5%

M	PRODUCT	Active	Appearance	Filtration	Binder	Sulfur Content	Density
Α		Content (%)		(µm)		(%)	(g/cm³)
S T	Actmix® ETU-75GN F140	75	White to Off-white Granules	140	NBR	23.0	1.15

* Binder type can be customized. Except NBR, others binders, such as EPDM/EVM, SBR, AR, ECO also can be available for.

SAFETY&TOXICITY:

Please refer to related SDS.

PACKAGING&STORAGE:

Net weight 25kg/PE bags lined carton; Net weight 600kg/pallet.

Shelf-life: 1 year in its original packaging

Stored in a dry and cool place.

Compared to traditional ETU powders, Actmix®ETU-75GN F140 allows:

Dust free products with a complete filtration up to 100µm, avoid bitter taste from inhalation, health guard of operators.

Effective guarantee of activity of ETU due to pre-dispersed masterbatch.

Tack free products at room temperature, convenience and accuracy on ingredients.

Lower Mooney viscosity at lower temperature (50°C), higher quality of dispersion.

Impurity free, blocked filter free of extrusive products, scrap rate reduction and higher productivity thanks to filtration. Wider compatibility with other elastomers.

G: granule, P: plate, E: EPDM binder, N: NBR binder, S: SBR binder, A: ACM binder, EO: ECO binder, F140: filtration and micron number of filter The information contained in this leaflet is based on tests carried out by our laboratories and data selected from references. Therefore it is not valid legally and does not signify any guarantee to customers of successful applications of the product according to their own formulas. However, our company will offer professional services in technology at utmost to facilitate customers to achieve expected purpose of product applications.

Actmix®ETU-75GN F140

TECHNICAL DATA SHEET(TDS)version 1.3