

304 Stainless Steel Explosion-Proof CCTV Mini Camera For Marine, Gas Station Camera WDM-EX700WB Model WDM-EX200HB Color 1/2.8" CMOS Sensor Color 1/3" CCD NVP2441+IMX322/IMX291 PAL/NTSC System Resolution 700TVL 1080P PAL: 795(H)×596(V) Effective pixels 1920*1080 **Features** / NTSC: 811(H) * 508(V) 700TVL/1080P High Resolution S/N Ratio 52dB(Min)/60dB(Max)(AGC ON/OFF) 52dB(Min)/60dB(Max)(AGC ON/OFF) 4/6mm lens for optional Lens 4/6mm lens for optional Explosion-proof housing IR Distance 30-60M IR Range 304 stainless steel surface treated with fluorine-Signal-to-Noise Ratio >75db **Electrical Connectivity** carbon spray. elegant structure. explosion proof, Composite cable dust proof, water proof, rust-proof... Rated Temperature -30 degree ~ +70 degree Optional temperature controlled SCR semiconductor Atmospheric Pressure 86~106kpa module to realize automatic heating and cooling Relative Humidity <=95%RH(+-25 degree) functions..heater turned on when temperature lower Material 304 Stainless steel than -10 degree +-5 degree Ingress Protection IP68 Can be installed on the market 80% camera Interface spec G-1/2" * We can customize right camera size according to Method of installation bracket mount II 2G Ex db IIC T6 Gb, II 2D Ex tb IIIC(85 degree) Db your requirement Atex Mark Ex dIIC T6 Gb/DIP A20 TA, T6 IEC Mark

Input Voltage
Working Current

DC12V

<=1A