



- * Hisilicon high-performance DSP
- * H.264 High profile dual stream
- * Standard ONVIF Protocol
- * Support motion detection, P2P, ONVIF
- * Support ICR filter switching function, day and night surveillance
- * Support remote control by smart phone, iPhone/Android
- * Support power supply DC12V
- * APP: XMEYE

Specification

Product Name	H.26 1.0/1.3/2.0MP Mini Detector Shaped IP Camera		
Model No.	WDM-IP64DTA	WDM-IP64DTB	WDM-IP64DTH
Video			
Items	Instruction		
System	Embedded linux		
Output resolution	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
D/N Mode	ICR-CUT		
Illumination	0.000LUX/F1.2(Led on)		
Video processing	H.264 video compression, dual streaming		
Video Output	Main streaming: 1280×720, 1024×768, 1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240	Main streaming: 1280×960, 1280×720, 1024×768, 1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240	Main streaming: 1920×1080, 1280×960, 1280×720, 1024×768, 1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access;		
	Support IE6.0 and above Smartphone		
	Support Android/iPhone		
Lens			
Lens	3.7mm high quality pinhole lens		
Function			
Function	Support motion detection		
	Support front end storage, playback and download		
	Support uniform client and platform system application		
Normal			
Power supply	DC12V		
Operation temperature	-10°C~+50°C		
Size	119mm×69mm/104mm×60mm		