

H.265 4X 2.0/4.0MP IR Bullet Security Surveillance HD IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.265/H.264 High profile
- *Support dual stream, support mobile phone
- *Support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification

Product Name	H.265 4X 2.0/4.0MP IR Bullet Wireless Wifi IP Camera	
Model No.	WDM-IP8001DZ	
Video		
System	Hisilicon high-performance DSP, Hi3516EV100+SC2235	Hisilicon high-performance DSP, Hi3516D+OV4689
Sensor	1/3" 2.0MP Progressive CMOS Image Sensor	1/3" 4.0MP Progressive CMOS Image Sensor
Output resolution	1920(H)×1080(V)	2592(H)×1520(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage	
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2	
Video processing	H.265/H.264 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable;	
Video Output	Main streaming: 1920*1080,1280*960, 1280*720,1024*768, 1280*720; Sub streaming: 960x540,640x360, 480*270,352*288,320*240,352*192, 320*192,288*192,256*192	Mainstreaming:2592*1520,2018*1536, 1920x1080, 1280x960, 1280*720, 1024*768, 1280*720; Sub streaming: 960*540,640*360, 480*270,352*288,320*240,352*192, 320*192,288*192,256*192
Frame rate	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	4.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported	
Access Protocol	Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and aboveSmartphone Support Android/iPhone	
Lens		
Lens	2.8-12mm auto iris lens	
IR distance	80m(4pcs 42mil Array)	
Function		
Function	Support WEB configuration, OSD,real-time video transmission	
	Support motion detection	
	Support front end storage ,playback and download	
	Support uniform client and platform system application	
	Support complete SDK for second development.	
	Support Wifi connection, meet with IEEE 802.11b/g wireless standard Support SD Slot, max 64GB SD Card	
Normal		
Power supply	DC12V/POE(optional)	
Operation temperature	-10°C~+60°C, 10%~90%RH	