

2.0MP/5.0MP 4X Optical Zoom Outdoor Bullet Waterproof IP PTZ Camera



Features

- * HD-IP bullet camera,outdoor, IP66
- * 1/3" CMOS, 2.0MP/5.0 Megapixels, 4X optical zoom
- * HD-IP digital interface output, 2.0/5.0MP high definition image
- * PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * IR distance 80M
- * Support P2P function,OSD menu is available
- * ONVIF2.4 compatible; good compatibility with NVRs like DAHUA HIKVISION , JUFENG and AXXON , Milestone and so on

Dimension



Accessories

- Instruction book
- Warrant card
- Screw fittings
- Desiccant

Product Name	2.0MP/5.0MP 4X Optical Zoom Outdoor Bullet Waterproof IP PTZ Camera	
Camera		
Model Number	WDM-IP8345THR-4X	WDM-IP8805MHR
Image Sensor	1/3" 2.0M pixels CMOS Hi3516C + Sensor Sony 323	1/3" 5.0M pixels CMOS Hi3516D + Sensor AR0521
Effective Pixels	2.0MP(1920X1080)	5.0MP(2592×1944)
Min. Illumination	Color: 0.05Lux@F1.2 ; D/N: 0.01Lux@F1.2	
Zoom	4X optical zoom, f= 2.7mm～13.5mm	
Day/Night	Day / Night / External control (IR Cut Filter)	
SNR	≥50dB(AGC OFF)	
WDR	Digital WDR≥70dB	
AGC	Auto / Manual	
White balance	Auto/Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp	
Digital noise Reduction	DNR, 3DNR	
Network		
Video Compression	H.265/H.264 Main Profile/M-JPEG	
Max Image Size	1920X1080@30fps	2592×1944@30fps
Streams	Dual streams	
Frame Rate	Main stream: 1920*1080, 1280*960, 1280*720,720*576, 640*480 Sub-stream: 640*480,480*360, 352*288, 320*240, 176*144	Main stream: 2592*1944, 1920*1080, 1280*960, 1280*720,720*576, 640*480 Sub-stream: 640*480,480*360, 352*288, 320*240, 176*144
Bitrate	CBR/VBR, bitrate: 32Kbps~10Mbps variable	
Audio Compression	G711, PCM	
P2P	Android / IOS	
Protocols	TCP/IP,HTTP, NTP,IGMP, DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,P2P	
Motion detect	Support	
Privacy Zone Masking	Support	
Onvif	Onvif 2.4	
IR parameters		
Night vision distance	80M	
Dome Features		
Pan Range	180° continued rotation	
Tilt Range	90° (Auto Flip)	
Manual pan speed	0.02~200°/S (1-64 degree variable)	
Manual tilt speed	0.02~120°/S (1-64 degree variable)	
Actual preset Accuracy	±0.10°	
Preset points	220	
Operation OSD language	Chinese /English	
General		
Certification	RoHs ,CE, FCC, IP66	
Work temperature	External-35Celsius degree~65Celsius degree	
Work Humidity	0%~95% (Non condensing)	
Temperature control	Intelligent control	
Power	DC 12V	
Consumption	≤ 20W	
Lightning Protection	Transient Voltage 6000V	