

法德镁 May www.wardmay.com

www.wardmay.com

| * Using the high performance sensor, image is clear and delicate; * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial anddistortion; * AHD/TVI/CVI/1200TVL 4 in 1 video output; * can access to many brands HD DVR; * Support the ultra low illumination; * Support automatic electronic shutter function, adapt to different monitoring environment; * 42pcs F5 ir led, 40m ir distance, DC12V |
|--|
| * Metal,Waterproof IP66 |

Specification

| Product Name | CCTV 2.0MP HD Video Security Surveillance IR Bullet AHD Camera | |
|---|--|--|
| Model No. | WDM-AHD6213U | |
| Video | | |
| Sensor | NVP2441H+Sony IMX322 | |
| Output resolution | 2.0MP (1920*1080) | |
| D/N Mode | IR cut Auto switching | |
| WDR | - | |
| DNR | 3D DNR | |
| Minimum Illumination | 0.001LUX/F1.2(Led on) | |
| | PAL: (1920*1080)@25fps | |
| Effective Pixel NTSC: (1920*1080)@30fps | | |
| Signal System | PAL/NTSC | |
| Video Standard | AHD/TVI/CVI/CVBS standard | |
| Video Output | 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable) | |
| Max Transmission Distance | Common 75-3 cables can be up to 500m | |
| Lens and IR | | |
| Lens | 2,8-12mm manual iris lens | |
| IR distance | 42pcs F5 ir led , 40m night vision distance | |
| Function | | |
| Shutter Speed | 4/25s-1/45,000s | |
| BLC | Off/Low/Medium/High/Highest | |
| White Balance | Auto White Balance | |
| HLC | Support | |
| Operation Temperature | -10°C~55°C | |
| Power Supply | DC12V | |