



- * Support 4ch 5.0MP/4chs 4.0MP video access/Support 2chs 5.0MP/4chs 4.0MP/16chs 960P access
- * POE Ethernet power supply; 4/8 standard POE ports
- * H.265
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support ONVIF Protocol; support GB28181 Protocol (Optional)
- * Support WEB, CMS, VMS, MYEYE Platform, provide SDK for develop
- * Support Mobile Phone Monitoring (IOS, Android)
- * Cloud Services, P2P, Alarm Information Push To Phone
- * Support Multi-Language
- * Support Multi-browser access (IE, Chrome, Firefox, Safari)

Specifications

Product Name	4/8ch H.265 Network PoE NVR	
Model No.	WDM-NVR7804T-YL/POE/VGA	WDM-NVR7808T-Q/POE/VGA

System

Processor	Hi3798M
Operating System	Embedded linux

Video

Video compression	H.265	
Video Input	4ch 5.0MP/4chs 4.0MP	2chs 5.0MP/4chs 4.0MP/16chs 960P
Playback	2ch 5.0MP/4chs 4.0MP	2ch 5.0MP/4chs 4.0MP/16chs 960P

Audio

Audio compression	G.711A
Voice intercom	Nonsupport

Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

Interface

HDMI output	1*HDMI (MAX: 5.0MP)	
VGA output	1*VGA (MAX: 1080P)	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
Poe	4*standard POE ports	8*standard POE ports
Audio In/Out	0/1	1/1
Alarm In/Out	0/0	
USB	2*USB2.0 ports	
HDD	1*SATA interface (Up to 8TB)	

General

Power supply	48V/1.5A	48V/2.5A
Consumption	<10W (Without HDD)	
Working temperature	0 ℃ - + 55 ℃	
Working humidity	10% -90% RH	
Chassis	Mini 1U	