



- * Support 4/8ch 1080P unreal-time encoding
- * Support XVI,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 1080P output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	4/8chs 1080P Network AHD DVR With 10" LCD Screen	
Model No.	WDM-DVR6504BL	WDM-DVR6508BL

System

Processor	Hi 3520DV300	Hi 3521A
-----------	--------------	----------

Video

Video compression	H.264	
Encode	4*1080P@15fps; 4*1080N	8*1080P@15fps; 8*1080N
Decode	4*1080P@15fps; 4*1080N	8*1080P@15fps; 8*1080N
Multi-mode	Analog: 4CH*1080P@15fps; 4*1080N	Analog: 8*1080P@15fps; 8*1080N
	Hybird: 2*1080P(analog) + 2*1080P(network)	Hybird: 4*1080P(analog)+ 4*1080P(network)
	IP: 16*1080P; 16*960P; 4*5MP	IP: 8*1080P+8*960P; 4*5MP
Playback	4ch	4ch

Audio

Audio compression	G.711A
-------------------	--------

Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

Interface

Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX: 1080P)	
VGA output	1*VGA (MAX: 1080P)	
Audio In/Out	1/1	4/1
Alarm In/Out	0/0	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB	2*USB 2.0 ports	
HDD	1*SATA interface (Up to 8TB)	

General

Power supply	DC12V 2A
Consumption	<10W(Without HDD)
Working temperature	0℃--+55℃
Working humidity	10%--90%
Weight	Around 1.8KG
Dimension	287mm(L)* 230mm(W)* 57mm(H)